







						
	WallPaper Flexible LED	Hybrid 15 Indoor/Outdoor	Linx - 18 Flexible LED	Linx - 30 Flexible LED	18mm PixelFlex LED Curtain	36mm PixelFlex LED Curtain
Pitch (mm)	10.12	15.0 (Spot - 150mm)	18.75	31.25	18.25	37.5
LED Type	3 in 1 SMD	3 in 1 SMD	3 in 1 SMD	3 in 1 SMD	3 in 1 SMD	3 in 1 SMD
Number of Pixels	32 x 16 (512) / Module	40 x 40 (6,400)/Tile	16 x 64 (1024) / Module	8 x 32 (256) / Module	64 x 128 (8196) / Panel	32 x 64 (4098) / Panel
Pixel Density	9,700	4,445	2,844	1,024	3,000	710
Dimensions	324mm x 162mm x 13mm (12.8" x 6.4" x 0.5")	600mm x 600mm x 125mm 23.6" x 23.6" x 4.9"	300mm x 1200mm x 14mm (11.8" x 47.3" x 0.6")	250mm x 1000mm x 11mm (9.8" x 39.4" x 0.5")	1.2m x 2.4m x 90mm (3.9' x 7.8' x 3.5")	1.2m x 2.4m x 90mm (3.9' x 7.8' x 3.5")
Brightness	1,500 NITS	2,800 NITS (Spot - 16 x 300lm)	4,500 NITS (Cree 5050)	3,000 NITS (Cree 5050)	3,500 NITS	1,200 NITS
AC Power In	100-240V	100-240V	100-240V	100-240V	100-240V	100-240V
Power Consumption	28 Watt / Tile Max	350 Watt / Tile Max	180 Watt	80 Watt	800 Watt / Panel Max	250 Watt / Panel Max
Weight/Tile	0.4 Kg (0.9 lbs)	9.8 Kg (21.6 lbs)	1.9 Kg (4.19 lbs)	1.9 Kg (4.19 lbs)	25 Kg (55 lbs)	12 Kg (26 lbs)
Colors	4.4 Trillion	281 Trillion	281 Trillion	281 Trillion	281 Trillion	281 Trillion
Refresh Rate	240Hz	4,000Hz	>1200Hz	>1200Hz	>240Hz	240Hz
Viewing Angle Vertical	>120°	140°	>120°	>120°	>120°	>120°
Viewing Angle Horizontal	>120°	140°	>120°	>120°	>120°	>120°
Transparency	--	--	40%	55%	--	--
Life Time	75,000	50,000	50,000	50,000	50,000	50,000

						
	Flex 12 Indoor/Outdoor	FlexMesh Indoor/Outdoor	Blade™ 1260 Indoor/Outdoor	25mm Indoor/Outdoor	Blade HD Mini Indoor/Outdoor	BO6 LED Floor Indoor/Outdoor
Pitch (mm)	12.50	50	12.50	12.50	12.50	6.25
LED Type	3 in 1 SMD	3 in 1 SMD			3 in 1 SMD	3 in 1 SMD
Number of Pixels	16 x 768 (12,288) / Header	24 x 192 (4,608) / Header	16 / Fixture	72 / Fixture	24 / Fixture	80 x 80 (6,400) / Tile
Pixel Density	6,400	400	2,560	2,560	2,560	25,600
Dimensions	200mm x 9600mm x 20mm (7.8" x 377.9" x .8")	1200mm x 9600mm x 20mm (47.2" x 377.9" x 8")	600mm x 31.25mm x 54mm (23.6" x 1.2" x 2.1")	900mm x 31.25mm x 54mm (35.4" x 1.2" x 2.1")	300mm x 31.25mm x 54mm (11.8' x 1.2' x 2.1")	500mm x 500mm x 83mm (19.7" x 19.7" x 3.3")
Brightness	5,000 NITS	1,200 NITS	6,000 NITS	6,000 NITS	6,000 NITS	4,000 NITS
AC Power In	100-240V	100-240V	100-240V	100-240V	100-240V	100-240V
Power Consumption	1200 Watt Max	1800 Watt Max	17 Watt Max	34 Watt Max	20 Watt Max	200 Watt / Tile Max
Weight/Tile	16.5 Kg (36.3 lbs) / SqM	6.7 Kg (14.7 lbs) / SqM	1 Kg (2.2 lbs) / Fixture	1.5 Kg (3.3 lbs) / Fixture	0.75 Kg (2.0 lbs)/Fixture	13.0 Kg (28.6lbs)
Colors	281 Trillion	281 Trillion	281 Trillion	281 Trillion	281 Trillion	4.4 Trillion
Refresh Rate	3,000Hz	3,000Hz	3,000Hz	3,000Hz	3,000Hz	>1,000Hz
Viewing Angle Vertical	>160°	160°	>140°	>140°	>140°	>120°
Viewing Angle Horizontal	>160°	160°	>140°	>140°	>140°	>120°
Transparency	--	44%	Variable	Variable	Variable	--
Life Time	50,000	50,000	50,000	50,000	50,000	50,000